

Permanent ultrasonic wastewater flow meter

FLUXUS[®] WW – Efficiency in monitoring wastewater flows

**Easy retrofit, no maintenance costs,
outstanding performance**

Very low installation costs

Maintenance-free

Non-intrusive

Measures fluids with gas
or solid content of up to 10%

Suitable for disturbed
flow profiles



FLEXIM

when measuring matters



FLUXUS® WW

For monitoring pump efficiency, controlling flow rates, and managing heavy rainfall events

Operators of sewage networks and treatment plants are striving to **improve the energy efficiency** of their systems. With pumps consuming a large amount of electrical energy, there is a strong demand to monitor and control the flow in pumping stations more accurately.

A further reason to equip pumping stations with flow meters is to be able to **react effectively in the event of heavy rainfall**. In such cases sewage levels at pumping stations can rapidly reach critical levels and operators need to know exactly how much each pump in their system is transporting in order to take appropriate action.

The FLUXUS® WW is the ideal flow meter for retrofitting at pumping stations and treatment plants. It is installed without pipe modification or intrusion, is maintenance-free and delivers accurate and reliable flow measurements.

Cost-efficient retrofitting

The FLUXUS® WW clamp-on ultrasonic flow meter is **installed without process interruption** or the need to carry out any work on the pipe itself. In pumping stations the installation conditions are often far from perfect, with a lack of straight pipe lengths and proximity to the pump. To **compensate for flow profile disturbances** the transmitter of the FLUXUS® WW series can be equipped with a second pair of transducers. This averages out the effects of crossflow and delivers a more repeatable measurement.

For installations in wet wells and other locations with potentially explosive atmospheres, transducers with **ATEX Zone 1 approval and IP68 protection** can be supplied.





Efficiency in flow monitoring

Permanently drift-free

The chemical composition of wastewater promotes the formation of scaling and fat deposits. Due to its higher solid content, especially sand, wastewater can also be abrasive. The clamp-on ultrasonic transducers of the FLUXUS® WW series, however, are **not impaired by scaling, fat deposits or abrasion** and therefore the measurements **remain permanently drift-free**.

Precisely matched piezo-transducers and an advanced factory calibration further contribute to the accuracy and long-term stability of the instrument. FLEXIM incorporates temperature sensors into every one of their ultrasonic transducers to compensate ambient temperature variations and ensure **unrivaled measurement repeatability**.

Outstanding performance

The advanced signal evaluation and noise reduction technology of the FLUXUS® WW makes it capable of **measuring fluids with high gas or solid content** (up to 10% in volume), such as return activated sludge (RAS). The FLUXUS® WW also measures flow in large PCCP or GRP pipes, which are composed of several layers of material and can have wall thicknesses of several centimeters.

The outstanding performance and efficiency of the FLUXUS® WW is made complete by an extensive set of diagnostic and evaluation functions. Contact your local FLEXIM support office for more details.

FLEXIM

More than 25 years of experience
in non-invasive ultrasonic flow measurement



Product variant:	FLUXUS® WW
Pipe diameter range:	up to 6500 mm
Pipe material:	All
Media:	Water / Wastewater
Solid or gas content:	up to 10 % in volume
Flow velocity:	0.01... 25 m/s
Accuracy:	± 0.5% of reading ± 0.01 m/s (field calibrated) ± 1.2% of reading ± 0.01 m/s (out of the box - application dependent)
Repeatability:	0.15 % of reading ± 0.01 m/s
Protection degree of transducers:	IP68 and ATEX zone 1 and 2 optional
Transmitter protection degree:	IP65
Number of flow measuring channels:	2
Communication options:	RS232, Modbus RTU
Data logger:	> 100.000 values
Outputs:	2x Current, 3x Binary

FLEXIM GmbH

Berlin, Germany
Phone: +49 30 93 66 76 60
info@flexim.de

FLEXIM Austria GmbH

Olbendorf, Austria
Phone: +43 33 26 529 81
office@flexim.at

FLEXIM Instruments Benelux B.V.

Berkel en Rodenrijs, Netherlands
Phone: +31 10 24 92 333
benelux@flexim.com

FLEXIM France SAS

Strasbourg, France
Phone: +33 3 88 27 78 02
info@flexim.fr

FLEXIM Instruments UK Ltd.

Northwich, UK
Phone: +44 1606 781 420
sales@flexim.co.uk

FLEXIM Middle East

Dubai, U.A.E.
Phone: +971 4430 5114
salesme@flexim.com

FLEXIM Instruments Asia Pte Ltd.

Singapore, Singapore
Phone: +65 67 94 53 25
salessg@flexim.com

FLEXIM Instruments China

Shanghai, China
Phone: +86 21 64 95 75 20
shanghai@flexim.com

FLEXIM S.A.

Santiago de Chile, Chile
Phone: +56 22 32 03 62 80
info@flexim.cl

FLEXIM AMERICAS Corporation

New York, USA
Phone: +1 63 14 92 23 00
salesus@flexim.com

FLEXIM Service and Support Center South America

Esco Argentina S.A., Buenos Aires
Phone: +54 11 49 20 71 00
flexim@escoarg.com.ar
www.escoarg.com.ar

www.flexim.com